

CoolantClean III MCF 5100

A Professional Coolant Flush Service Center

- ▶ Complete Coolant Exchange In Less Than 15 Minutes
- ▶ Unique Vacuum Switch Allows For Cooling System Depressurization
- ▶ One Multi-Function Switch Operation
- ▶ One Top-off Switch
- ▶ "Closed Loop" Mode At End of Service
- ▶ Portable, Operates On 12 Volt DC Power
- ▶ Easy Connection Though Radiator Hose
- ▶ Internal Waste Tank
- ▶ Easy Service Filter
- ▶ Sturdy, Compact Design
- ▶ Comprehensive Adapter Kit For Most Cars



Part# 400-0128

The CoolantClean Service Kit includes specifically formulated solutions for the CoolantClean III that can also be safely used in other coolant exchange machines.



Part No. 500-5100P

▶▶ MOTORVAC COOLANTCLEAN III MCF 5100

Why Use the Motorvac CoolantClean System?

CoolantClean is designed to exchange virtually all of the used coolant mixture in a vehicle's cooling system, and do it in only a few simple steps! The CoolantClean coolant flush service can increase a shop's profits by reducing the time it takes to do a complete fluid exchange to approximately 15 minutes. This new turn-key radiator service system is easy to use and compatible with most automotive vehicles.

How Motorvac CoolantClean Works

CoolantClean's advanced flush system allows complete control. CoolantClean connects through the upper radiator hose and provides a clean, "environmentally friendly" and systematic approach to servicing cooling systems. The unit will flush virtually all of the old coolant and replace it with the new coolant mixture in just a few easy steps!

Normally, when a technician drains coolant from a vehicle, the process is time consuming, incomplete, messy and dangerous. The CoolantClean system changes all that. With CoolantClean, the process is quick, easy and safe. CoolantClean completes the fluid exchange faster and completely, even replacing the old coolant from the engine block and heater core. CoolantClean also has a unique vacuum system, which allows for radiator depressurization and reservoir fluid evacuation.

CoolantClean Solutions

MotorVac provides two solutions that when used will further enhance the CoolantClean service. A specially formulated radiator flush restores cooling system efficiency by removing rust, scale and other residues. A lubricant conditioner will help prevent rust and corrosion while lubricating the water pump. The solution also contains inhibitors that help prevent radiator deposits that cause clogging and overheating. Used together these solutions will improve overall maintenance of the coolant system and extend radiator life.

Features

- Static or dynamic fluid exchange
- One switch, multi-function operation with "closed loop" mode at end of service
- Unique "vacuum switch" regulates system depressurization and fluid evacuation
- Complete flow synchronization maintains a 1-to-1 fluid ratio exchange
- Front panel controls all machine functions with pressure gauge and warning lights
- Industrial grade radiator hoses & adapters included to service most vehicles
- Dual pump operation
- Pressure is limited to 10 psi – if cap malfunctions, fluid will overflow into reservoir
- Vacuum is used to minimize clogging and potential damage to system components

Benefits

- Free 1-800 Technical Support Team
- Simple – Connects through the radiator hose in about 2 minutes
- Easy – Accessible function switches control all operations on the front panel
- Safe – No spilled coolant on the floor and re-circulation protects the system
- Fast – Complete coolant exchange service takes less than 15 minutes
- Portable – Unit is powered by a 12 volt DC battery so you can use it anywhere
- Convenient – No bay space is required to perform complete service
- Reliable – 100% exchange provides the highest quality service to your customers

Technical Specifications

- ▶ Power Cord - 10 ft. (3.048m.) 14 Gauge
- ▶ Power Supply - 12 Volt DC Operation
- ▶ Circuit Protection - 15 Amp Circuit Breaker
- ▶ Hoses - 4 ft. (2.43 m.) Output and Return with Quick Coupling
- ▶ Hose - 6 ft. (1.82m.) Clear Braided Drain Hose (With Check Valve to Prevent Leakage)
- ▶ Tank - 2 - 26 Quart Coolant Fluid
- ▶ Coolant Pump - 76.8 Gallons Per Hour (290.7 l.) Low Pressure
- ▶ Vacuum Pump - 76.8 Gallons Per Hour (290.7 l.) Low Pressure
- ▶ Gauge - 2 in. Diameter (30 psi / 2 bar)
- ▶ Filter - External Coolant Filter
- ▶ Ship Weight - 85 lbs. (38.5 kg.)
- ▶ Ship Height - 41" (104.14 cm.)
- ▶ Ship Width - 24" (60.96 cm.)
- ▶ Ship Depth - 19" (48.26 cm.)
- ▶ Cabinet - Rotomolded
- ▶ One Year Limited Warranty

Adapters

The Standard Adapter Kit covers most vehicles and the Heavy Duty Adapters are for large trucks and are available for purchase.



STANDARD KIT
(INCLUDED)
Part No. 200-3103



HEAVY DUTY ADAPTERS
(OPTIONAL)
Part No. 200-8803



MotorVac Technologies
1431 South Village Way, Santa Ana, CA 92705 USA
tel 714-558-4822 800-841-8810 fax 714-558-0754 ▶ www.motorvac.com
©2009 MotorVac Technologies. MotorVac and CoolantClean are registered trademarks of MotorVac Technologies



RO# MT5100SS