



MONTY 3300-26 RACING TYRE CHANGER



FEATURES

- **Smartspeed** - This revolutionary, patent-protected technology optimises the applied torque on the wheel and automatically establishes the maximum rotational speed of the wheel.
- **Adjustable Clamping Jaws** - Four self-centring, three-way adjustable jaws provide a clamping range from 10 to 26 inches. Our system minimises cylinder stroke for faster clamping and features a compact turntable to reduce machine footprint.
- **On-floor Bead Breaker** - Our premium on-floor bead breaker features a pedal-operated design for hands-free operation, a wide bead breaker pad for stability, and five shovel adjustment axes for precision. The high pad offset prevents interference between the tyre and the turntable cylinder, and the ergonomic pedal positioning enhances operator comfort.
- **Easymont** - Comprised of a new bead pressing tool with lifting hook, hex roller, top roller, and lifting disk, the new easymont™ 330 pro streamlines the mounting and demounting of low-profile and high-performance tyres, enabling a single technician to perform tasks with ease.
- **New Pressing Tool** - The updated easymont™ 330 pro pneumatic bead assist features a new pressing foot style optimised to prevent tool slippage that could damage tyres and wheels.
- **Flexion Guard** - The tilt-tower provides high rigidity with a reinforced horizontal arm that prevents flexions of the system when working on run-flat and highperformance tyres.

SPECIFICATIONS

| | |
|----------------------------------|------------------|
| Max Rim Diameter | 66cm |
| Max Tyre Width | 38cm |
| Max Rim Width | 35cm |
| Max Wheel Diameter | 112cm |
| Wheel Lift Capability (optional) | 70kg |
| Power Supply | 230V 1ph 50-60Hz |
| Air Pressure Required | 8-12 bar |
| Dimensions HxWxD | 182x159x171cm |

CALL LOGICAR FOR MORE INFORMATION

☎ 1300 322 782

