

ARIAZONE 601 HD (R134a)

A lightweight, durable refrigerant recovery/recycle unit ideal for the mobile specialist or small workshop professional

The unit is suitable for servicing passenger and commercial vehicle air-conditioning systems.

KEY FEATURES

- Integrated suction and discharge pressure gauges
- High-capacity heat exchangers for efficient performance
- Oversized filter drier for improved moisture and contaminant removal
- Heavy-duty recovery pump with built-in thermal overload protection
- Liquid control protection safely recovers both liquid and vapour refrigerant
- High-pressure safety cut-out system
- Large condenser and cooling fan for faster refrigerant recovery
- Automatic recovery completion shut-off with indicator
- Self-purge function to prevent cross-contamination
- Robust, heavy-duty steel construction with durable protective coating



SPECIFICATIONS

Model No.	601 HD (R134a)
Refrigerant	R134a
Recovery Pump	Danfoss - TL5G
Recovery Rate	210 grams/min (liquid state)
Inbuilt Oil Separator	AI 100/76/1 (sinter bronze separator)
Inbuilt Large Filter Dryer	AI 162-1/4" (solid core)
Refrigerant Recovery Rate	0.22kg (0.5lb) /min (liquid state at 25°C)
Self Cleaning	Self purge feature with ball valve
Service hoses with ball valves	Suction 150cm (5 ft), Discharge 90cm (3 ft)