



GEODYNA 7340L/P WHEEL BALANCER



FEATURES

- RECOMMENDED BY OPEL
- easyWeight: Pinpoint laser light indicator to accurately and conveniently position adhesive weights on the wheel
- Intuitive dual 3-digit LED display for the amount readings and bright weight position indicators – integrated in the weight tray
- Semi-automatic input of offset and rim diameter via 2D SAPE and automatic rim width acquisition via Smart Sonar – fast and easy
- Semi-automatic pre-selection of balancing mode via easyAlu
- Imbalance minimisation and optimisation programs
- VPM measurement technique for uncompromised accuracy
- QuickBal for reduced measurement time: Short start-stop cycle time: 4.5 seconds (15" rim)
- New ergonomic weight tray
- Clamping of wheel on integrated flange with quick nut
- Finish RAL 7035

SPECIFICATIONS

Manual Rim Diameter Range	20 - 81.2cm
Manual Rim Width Range	2.5 - 50.8cm
Max. Wheel Diameter	107cm
Semi-Automatic Rim Diameter Range	20 - 63.5cm
Semi-Automatic Rim Width Range	7.6 - 38cm
Max. Wheel Weight	70 kg
Power Supply	115V 1Ph 60Hz

CALL LOGICAR FOR MORE INFORMATION

📞 1300 322 782